



Note. Operating pressure 0.4–0.7 MPa G
 Valve open : Port (a) Exhaust Port (b) Supply
 Valve close : Port (a) Supply Port (b) Exhaust

157	SCREW (F)	4	STAINLESS STEEL (SUS304)	
1a	RING	2	STEEL (SS400) with Epoxy Powder Coat.	
39	BOLT·NUT (P)	4sets	STAINLESS STEEL (SUS304)	
38	BOLT (E)	4	STAINLESS STEEL (SUS304)	
37a	SCREW (C)	1	STAINLESS STEEL (SUS304)	
37	JOINT (A)	1	COPPER ALLOY (C3604)	
35	ACTUATOR	1	CAST IRON (FC200) etc.	Acryl Coat.
30	STAND	1	CAST ALUMINIUM ALLOY (AC4C)	Epoxy Coat.
8	STEM HOLDER (A)	1	PP	
7	STEM	1	STAINLESS STEEL (SUS403)	
6	O-RING (C)	1		
5	O-RING (B)	2	□EPDM □FKM	
4	O-RING (A)	2	□Others ()	
3	SEAT	1		
2	DISC	1	BODY/DISC □PP/PP	
1	BODY	1	□PVDF/PVDF	
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

DIMENSIONS TABLE

Unit : inch

Nominal Size	ANSI Class 150				L	D	D ₁	D ₂	H	H ₁	A	A ₂	A ₃	P	Actuator Type
	d	C	n	h											
16" 400mm	15.98	21.25	16	1.12	6.65	23.62	18.50	9.25	29.80	11.81	26.14	5.47	3.35	3/8	TA-200D

ITEM	BUTTERFLY VALVE (TYPE56) PNEUMATIC MODEL TA TYPE ASS'Y DOUBLE ACTING ANSI Class 150 : 16" (400mm)		
DRAWN	E.Ozaki	DATE	SCALE
CHECKED	H.Kawano	JAN.22.2018	~
APPROVED	H.Kourogi	DRAWING No. 56-AA001AE	
SPECIAL ORDER No.	ASAHI YUKIZAI CORPORATION		