



1b	INSERTED METAL OF BODY	4	COPPER ALLOY (C3604)	Used for JIS 10K
131	STEM HOLDER (C)	1	PP	
24	CAP (A)	1	PP	
23	SCREW (B)	4	STAINLESS STEEL (SUS304)	
22	LOCKING PLATE	1	PPG	
21	BOLT (B)	1	STAINLESS STEEL (SUS304)	
20	WASHER (A)	1	STAINLESS STEEL (SUS304)	
19	SPRING	1	STAINLESS STEEL (SUS304)	
18	PIN	1	PPG	
17	HANDLE LEVER	1	PPG	
16a	INSERTED METAL OF HANDLE	1	STAINLESS STEEL (SUS316)	
16	HANDLE (A)	1	PP	
9	BOLT (A)	3	STAINLESS STEEL (SUS304)	
6	O-RING (C)	1	□EPDM □FKM □others ()	
7	STEM	1	PP	
2	DISC	1	PP	
1	BODY	1	PP	
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

DIMENSIONS TABLE

Unit: mm

Nominal Size	JIS 5K				JIS 10K				M	D	D1	L	H	H1	H2	H3	A		
	d	C	n	h	C	h	N	N											
400mm 16"	394	495	16	25	510	27	16	14	2	4	M24	600	470	157	451	300	382	69	400

ITEM	ROTARY DAMPER (TYPE56) ASS'Y LEVER TYPE : □JIS 5K, □JIS 10K 400mm (16")		
DRAWN	M.Yamamoto	DATE	SCALE
CHECKED	H.Kawano	JUL.6.2010	~
APPROVED	Y.Ozaki	DRAWING No. DP-M1001JE	
SPECIAL ORDER No.	ASAHI YUKIZAI CORPORATION		