



131	STEM HOLDER (C)	1	PP	
24	CAP (A)	1	PP	
23	SCREW (B)	4	STAINLESS STEEL (SUS304)	
22	LOCKING PLATE	1	PPG	
21	BOLT (B)	1	STAINLESS STEEL (SUS304)	
20	WASHER (A)	1	STAINLESS STEEL (SUS304)	
19	SPRING	1	STAINLESS STEEL (SUS304)	
18	PIN	1	PPG	
17	HANDLE LEVER	1	PPG	
16	HANDLE (A)	1	PP	
14	GLAND	1	PVDF	
13	SPACER (A)	1Set	C-PVC	
12	V-PACKING	1Set	PTFE	
10	BUSH (A)	1	PVDF	
9	BOLT · NUT (A)	3Sets	STAINLESS STEEL (SUS304)	
7	STEM	1	PVDF	
2	DISC	1	PVDF	
1	BODY	1	PVDF	
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

ITEM	ROTARY DAMPER (TYPE 75) ASS'Y LEVER TYPE : DIN PN10 450 <sup>mm</sup> (18") ~ 600 <sup>mm</sup> (24")		
DRAWN	M.Oosako	DATE	SCALE
CHECKED	H.Kawano	NOV.15.2010	~
APPROVED	Y.Ozaki	DRAWING No. DP-M1003DE	
SPECIAL ORDER No.	ASAHI YUKIZAI CORPORATION		

DIMENSIONS TABLE

NOMINAL SIZE	DIN PN10				UNIT : mm									
	d	C	n	h	D	D <sub>1</sub>	D <sub>2</sub>	L	H <sub>1</sub>	H <sub>2</sub>	H <sub>3</sub>	H	A	
450 <sup>mm</sup> 18"	441	565	20	26	630	525	340	167	315	422	69	491	400	
500 20	488	620	20	26	680	575	340	177	350	452	69	521	400	
600 24	600	725	20	30	790	686	340	197	424	517	69	586	400	

NOTE. The shape and appearance of assembly differ a little with nominal size compared to this drawing.