Safety Data Sheet

Conforms to JIS Z 7253: 2019

No.D-001e-13

Preparation date: May 14, 2010 Revision date: June 16, 2023

Page : 1/9

1. Chemicals and Company Information

Product identifier AV Adhesive 32 (low-viscosity quick-drying up)

SDS No. No.D-001

Supplier name Asahi Yukizai Corporation

Address 2-5955, Nakanose-cho Nobeoka-city Miyazaki-pref. Japan 882-8688

Phone number +81-982-35-9380

(EHS Management Department Valve & Piping Systems Division)

Fax number +81-982-35-9358

(EHS Management Department Valve & Piping Systems Division)

Emergency phone number +81-982-35-9380

Manufacturer Konishi Co., Ltd.

Recommended use and restrictions on useAdhesive for PVC pipes. Use only as specified.

2. Hazards Identification

GHS classification and label elements of the product

Physical hazards Flammable liquids : Category 2

Health hazards Skin corrosion/irritation : Category 2

Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 2
Skin sensitization : Category 1
Germ cell mutagenicity : Category 2
Reproductive toxicity : Category 2
Specific target organ toxicity (single exposure)

: Category 1 (respiratory system)

Specific target organ toxicity (single exposure)

: Category 2 (kidney, central nervous system)

Specific target organ toxicity (single exposure)

: Category 3 (anesthetic effect)

Specific target organ toxicity (single exposure)

: Category 3 (airway irritability)

Specific target organ toxicity (repeated exposure)

: Category 1 (respiratory system, central nervous system,

gastrointestinal tract, bone, nervous system)

Items for which the GHS classification result is "Not applicable to classification" or "Cannot classify" are not listed.

GHS label elements Symbol (GHS JP)







GHS02

Danger

GHS07

GHS08

Signal word (GHS JP)

Hazard statement (GHS JP)

H225: Highly flammable liquid and vapor

H315: Causes skin irritation

H317: May cause allergic skin reactions. H319: Causes serious eye irritation

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

No.D-001e-13

Preparation date: May 14, 2010 Revision date: June 16, 2023

Page : 2/9

H335: May cause respiratory irritation

H336: May cause drowsiness or dizziness.

H341: Suspected risk of hereditary disease

H361: Suspected of causing adverse effects on fertility or the unborn child.

H370 : Organ damage (respiratory system)

H371: Risk of organ damage (central nervous system, kidney)

H372 : Organ damage due to long-term or repeated exposure

(respiratory system, central nervous system, gastrointestinal tract, bones, nervous system)

Precautionary statement (GHS JP) Safety measures

P201: Obtain the instruction manual before use.

P202: Do not handle until all safety precautions have been read and understood.

 $P210\,:\,Keep$ away from heat / sparks / open flames / hot surface.

- No smoking.

P233: Keep container tightly closed.

P240: The container shall be grounded and earthed.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use tools that do not generate sparks.

P243: Take measures against electrostatic discharge.

P260 : Do not inhale mists/vapors/sprays. P261 : Avoid inhalation of mist/vapor/spray.

P264: Wash hands, forearms and face thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be removed from the workplace.

P280: Wear protective gloves.

First-aid measures

P302+P352: If on skin, wash with plenty of soap and water.

P303+P361+P353: If on skin (or hair), take off immediately all

contaminated clothing. Rinse skin with water/shower.

P304+P340: If inhaled, remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: If in eyes, rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P311: If there is exposure or concern of exposure, contact a physician.

P308+P313 : If there is exposure or concern of exposure, get medical advice/attention.

P312: Call a doctor if you feel unwell.

P314: Get medical advice/attention if you feel unwell.

P321: Specific treatment is required.

P332+P313: If skin irritation occurs, get medical advice/attention.

P333+P313: If skin irritation or rash occurs, get medical advice/attention.

P337+P313: If eye irritation persists, get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P370+P378: In case of fire, use appropriate media other than water for

extinction.

Storage

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal

P501 : Dispose of contents/container in accordance with local/national regulation.

Summary of significant candidates and possible emergencies

The product may cause organic solvent poisoning.

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

No.D-001e-13

Preparation date: May 14, 2010 Revision date: June 16, 2023

Page : 3/9

3. Composition / Information on Ingredients

Single or Mixture Mixture

Product name Vinyl chloride resin adhesive

	Concentration	Chemical	Reference Number in Gazetted List in Japan		
Component	or concentration range		CSCL (Chemical Substances Control Law)	Labor Safety and Health Act	CAS No.
Methyl ethyl ketone	40-50%	CH ₃ CH ₂ COCH ₃	(2)-542	-	78-93-3
Cyclohexanone	20-30%	C ₆ H ₁₀ O	(3)-2376	-	108-94-1
Acetone	10-20%	CH ₃ COCH ₃	(2)-542	-	67-64-1

4. First-aid Measures

Description of first-aid measures

If inhaled Remove person to fresh air and keep comfortable for breathing.

Get a doctor/physician if you feel unwell.

If on skin Call a doctor immediately.

Wash gently with plenty of soap and water. Remove all contaminated clothing immediately.

Wash skin with running water/shower.

If in eyes Rinse cautious with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Call a doctor immediately.

If swallowed Rinse mouth.

Contact a physician immediately.

Do not induce vomiting.

Protection of first-aiders Wear appropriate protective equipment.

5. Fire-fighting Measures

Extinguishing media

Suitable extinguishing media Powdered chemical fire extinguisher, carbon dioxide or ordinary foam fire

extinguisher, sand/soil.

Un suitable extinguishing mediaDo not use direct water jet.

Fire Hazards Extremely flammable liquid and vapor.

Extinguishing Measures In the event of fire, stop the leak if it can be safely handled.

Conduct fire fighting from a safe distance and protected location.

Protective equipment for fire-fightersCompressed air and oxygen breathing apparatus

Wear fire/flame resistant/retardant clothing.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Non-emergency responder

Protective equipment Wear appropriate protective equipment when working.

First aid measures Avoid contact with skin and eyes.

Ventilate spilled area.

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

No.D-001e-13

Preparation date: May 14, 2010 Revision date: June 16, 2023

Page : 4/9

Do not touch or walk on spilled product. Prohibit entry of non-related personnel.

Environmental precautions

Environmental precautions Prevent entry into sewers and public waterways.

Prevent entry into drains or waterways.

Do not release the product into the environment.

Containment and cleanup methods and equipment

Containment methods In the event of a large spill, contain the spill in a trench and block it with

moist sand or earth for safe disposal afterwards.

Contain the leak without risk if possible.

Purification methodsIf a small amount of liquid is spilled, absorb it with a nonflammable

absorbent and place it in a container for disposal. Absorb all diffused product with sand or soil. Ground all equipment used when handling spills.

7. Precautions for Handling and Storage

Handling

Engineering measuresUse local exhaust ventilation and general ventilation as described in

"8. Exposure controls / Protective measures".

Take equipment measures as described in "8. Exposure controls

/ Protective measures" and wear protective equipment.

Precautions for safe handling Do not get on eyes, skin, or clothing.

Do not inhale dust/smoke/gas/mist/vapor/spray. Ensure adequate ventilation of work area.

Keep away from ignition sources such as heat/sparks/open flames/high

temperature items.

—No smoking.

No fire and pay attention to static electricity. Refer to "10. Stability and Reactivity."

Sanitary measures Always wash your hands after handling.

Storage

Safe storage conditions Store in a well-ventilated area.

Keep container tightly closed.

Keep out of sunlight.

Storage temperature 2-40 °C

8. Exposure controls / Protective measures

Methyl ethyl ketone (78-93-3)		
Control concentration (MHLW)	200ppm	
Allowable concentration (Japan Society for Occupational Health)	200ppm (590mg/m³)	
ACGIH	TWA 200ppm, STEL 300ppm	

Cyclohexanone (108-94-1)		
Control concentration (MHLW)	20ppm	
Allowable concentration (Japan Society for Occupational Health)	25ppm (100mg/m³)	
ACGIH	TWA 20ppm, STEL 50ppm (Skin)	

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

No.D-001e-13

Preparation date: May 14, 2010 Revision date: June 16, 2023

Page : 5/9

Acetone (67-64-1)	
Control concentration (MHLW)	500ppm
Allowable concentration (Japan Society for Occupational Health)	200ppm (470mg/m³)
ACGIH	TWA 250ppm, STEL 500ppm

Equipment measures Provide adequate ventilation.

Install a local exhaust system.

Personal protective equipment Wear the recommended personal protective equipment.

Hand protection Wear appropriate protective gloves.Eye protection Wear appropriate safety glasses.

Protective equipment for skin and bodyWear long-sleeved work clothes, and protective clothing / protective boots as

necessary.

Respiratory protection [If ventilation is inadequate] Wear protective equipment for breathing.

9. Physical and Chemical Properties

Physical state Liquid
Appearance Liquid

Color Colorless and semitransparent

Odor Petroleum odor

pH No data
Melting point No data
Freezing point No data
Boiling point No data

Flash point -20°C (minimum ignition point used)

Spontaneous combustion pointNo dataDecomposition temperatureNo dataFlammabilityNo dataExplosion limits (vol%)No dataSteam pressureNo dataRelative densityNo data

Relative Vapor density (20°C) 1 or more (air =1)

Density 0.89g/cm³ **Relative gas density** No data

Solubility Insoluble in water, soluble in organic solvent

n-octanol/water partition coefficient (LogPow) No data

Kinematic viscosity $100 \sim 250 \,\mathrm{mPa \cdot s}$

Dynamic viscosity measurement temperature 20°C

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

No.D-001e-13

Preparation date: May 14, 2010 Revision date: June 16, 2023

Page : 6/9

Dynamic viscosity rateNo dataParticle sizeNo dataParticle diameter distributionNo dataParticle shapeNo dataParticle aspect ratioNo dataParticle specific surface areaNo data

10. Stability and Reactivity

Reactivity Under normal conditions of use, storage and transportation, this product will

not react.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactionsStable under normal conditions of use.

Conditions to avoid Not applicable.

Incompatible materials Avoid contact with oxidizer.

Hazardous decomposition productsCarbon monoxide (CO).

11. Toxicological Information

Acute toxicity (oral)Cannot classifyAcute toxicity (dermal)Cannot classify

Acute toxicity (inhalation) Cannot classify (gas)

Cannot classify (vapor) Cannot classify (dust, mist)

Skin corrosion / irritation Skin corrosion

Serious eye damage / eye irritation Strong eye irritation

Respiratory sensitization Cannot classify

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Suspected hereditary disease

Carcinogenicity Cannot classify

Reproductive toxicity Suspicion of adverse effects on reproductive functions or the fetus

Specific target organ toxicity (single exposure) Organ damage (respiratory system)

Risk of organ damage (central nervous system, kidney)

May cause drowsiness or dizziness. Risk of irritation to the respiratory tract

Specific target organ toxicity (repeated exposure) Organ damage due to long-term or repeated exposure (respiratory system,

central nervous system, gastrointestinal tract, bones, nervous system)

Aspiration hazard Not applicable to classification

12. Environmental Impact Information

Ecosystems - GeneralWhen leaking or disposing of the product, be careful not to handle it as it

may affect the environment.

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

No.D-001e-13

Preparation date: May 14, 2010 Revision date: June 16, 2023

Page : 7/9

Hazardous to the aquatic environment Short-term hazard (Acute) Cannot classify

Hazardous to the aquatic environment Long-term hazard (Chronic) Cannot classify

AV Adhesive 32	
Residual and degradability	No data
Bioaccumulative	No data
Mobility in the soil	No data

Hazardous to the ozone layer

Cannot classify

13. Disposal Considerations

Contaminated container and package

Paper containers and packaging such as outer boxes and paper tubes:

Collected or disposed of as paper waste (If it is a single substance, it is treated as stable industrial waste. If there is an adhering component, it is also treated as controlled industrial waste too.)

When disposing of empty containers, remove the contents completely and dispose of them as industrial waste or send them for collection.

Metal can, metal drum, and metal tubes: Dispose of as scrap metal. (In the case of a single component, treat as stable industrial waste. If there are adhering components, follow the classification of stable/managed industrial wastes.)

Glass containers: Disposed of as glass waste. (In the case of a single component, treat as stable industrial waste. If there are adhering components, follow the classification of stable/managed industrial wastes.)

Plastic bottles, tubes, bags, etc.: Dispose as waste plastics. (In the case of a single component, treat as stable industrial waste. (If there are adhering components, follow the classification of stable/managed industrial wastes.)

Dispose in accordance with applicable laws and regulations and municipal standards.

Entrust disposal to an industrial waste disposer licensed by the prefectural governor, or to a local public body, if such a body is in charge of disposal.

When disposing of waste, follow the Law Concerning Waste Disposal and Public Cleansing in particular.

When disposing of the product, confirm the reactivity of the hazardous information before processing.

14. Transport Information

International regulations

Waste from residues

Road transport (UN RTDG)	Marine transport (IMDG)	Air transport (IATA)
UN No.		
1133	1133	1133
UN official product name		

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

No.D-001e-13

Preparation date: May 14, 2010 Revision date: June 16, 2023

Page : 8/9

Adhesives	ADHESIVES	Adhesives		
Classification of dangerous goods for transportation				
3	3	3		
2				
Packing group				
II	II	II		
Environmental Hazardous				
Environmental Hazardous	Environmental Hazardous	Environmental Hazardous		
Not applicable	Not applicable	Not applicable		
	Marine Pollutants			
	Not applicable			

Marine Pollutants Not applicable

Special transport precautions Follow the instructions in "7. Precautions for Handling and Storage"

Check that the containers are free from leakage and load them so as to prevent them from toppling over, falling, and suffering damage and ensure the prevention of cargo collapse.

the prevention of cargo collapse.

Domestic Regulations Land Regulations

When the Fire Service Law, Industrial Safety and Health Law, or Poisonous and Deleterious Substances Control Law is applicable, the product shall be transported in accordance with the applicable laws and regulations.

Maritime Regulation Follow the provisions of the Ship Safety Law.

Aviation Regulations Follow the provisions of the Civil Aeronautics Act.

Emergency Response Guideline Number 128

Other Information No supplementary information

15. Regulatory Information (in Japan)

Industrial Safety and Health Low

Second class organic solvent, etc. (Enforcement Ordinance, Schedule 6-2; Ordinance on the Prevention of Organic Solvent Poisoning, Article 1, Paragraph 1, Item 4)

Working Environment Assessment Standard (Article 65-2, Paragraph 1 of the Law)

Hazardous and toxic substances whose names must be indicated (Article 57-1 of the Law; Article 18 of the Enforcement Ordinance)

Hazardous / flammable material

(Enforcement Ordinance, Schedule 1, Item 4)

Hazardous and toxic substances whose names must be notified

(Article 57-2 of the Law; Enforcement Ordinance, Article 18-2, Schedule 9)
Acetone (Government Ordinance No. 17) $(10\sim20\%)$ Cyclohexanone (Government Ordinance No.231) $(20\sim30\%)$ Methyl ethyl ketone (Government Ordinance No.570) $(40\sim50\%)$

AV Adhesive 32

ASAHI YUKIZAI CORPORATION

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

No.D-001e-13

Preparation date: May 14, 2010 Revision date: June 16, 2023

Page : 9/9

Poisonous and Deleterious Substances Control Law Not applicable

Fire Service Act Category 4, Class 1 petroleum (water-insoluble) No fire Hazard class II

Foreign Exchange and Foreign Trade Act Export Trade Control Order, Appended Table 1-16

Ship Safety Act Flammable liquids (Regulations for the Carriage and Storage of Dangerous

Goods in Ships, Articles 2 and 3; Hazardous Materials Notification,

Schedule 1)

Civil Aeronautics Act Flammable liquids (Civil Aeronautics Law Enforcement Regulations, Article

194; Hazardous Materials Notification - Schedule 1)

Act on Port Regulations Other hazardous materials / flammable liquids (Article 21-2 of the Law;

Article 12 of the Regulations; Notification specifying the types of dangerous

goods, separate table)

Pollutant Release and Transfer Register Not applicable

16. Other Information

The evaluation of hazards and hazardous properties is not always satisfactory, so please handle with care.

If you have a Safety Data Sheet for this product that was previously given to you, please destroy it.

The SDS is subject to revision due to changes in laws and regulations, product improvements, etc.

If the date of creation or revision is more than two years ago, please confirm that it is the latest version.

SDS transmission route: In principle, Safety Data Sheets (SDS) are transmitted to end users through the following route.

If you have not obtained the SDS yet, please contact us through the sales channel to request the SDS or to inquire about the latest version.

(Manufacturer → agency → handling business)

Disclaimer

The information contained in this sheet is based on reliable information, but no warranty, express or implied, is given as to the accuracy of the information. Because the conditions under which the product is handled, used, stored, or disposed of are beyond our control and may not be known to us, we assume no responsibility, direct or indirect, for any loss, damage, or expense resulting from the handling, use, storage, or disposal of the product. This sheet should be used only with this product. If this product is used as an ingredient in other products, the information contained in this sheet may not apply.