



DIMENSIONS TABLE

Unit : mm

Nominal Size	Product indication	D		t		Approximate I.D. (for reference)	L		Weight (Kg/m)
		Basic Dimension	For average	Basic Dimension	Tolerance		Basic Dimension	Tolerance	
15mm	d20	20	± 0.3	1.9	± 0.4	16.2	4000	± 10	0.110
20	d25	25	± 0.3	2.3	± 0.5	20.4			0.166
25	d32	32	± 0.3	3.0	± 0.5	26.2			0.271
32	d40	40	± 0.4	3.7	± 0.6	32.6			0.421
40	d50	50	± 0.5	4.6	± 0.7	40.8			0.649
50	d63	63	± 0.6	5.8	± 0.8	51.4			1.028
65	d75	75	± 0.7	6.9	± 0.9	61.4			1.447
80	d90	90	± 0.9	8.2	± 1.1	73.6			2.083
100	d110	110	± 1.0	10.0	± 1.2	90.0			3.099
125	d140	140	± 1.3	12.8	± 1.5	114.6			5.008
150	d160	160	± 1.5	14.6	± 1.7	130.8			6.529
150	d180	180	± 1.7	16.4	± 1.9	147.2			8.250
200	d225	225	± 2.1	20.5	± 2.3	184.0			12.864

Note:

1. DIN8077
2. SDR(Standard Dimension ratio is the ratio of pipe diameter to wall thickness. (D/t)
3. 150mm (d160) is for spigot end, 150mm (d180) is for socket end.

No.	DESCRIPTION	QTY.	MATERIAL	REMARKS
	POLYPROPYLENE		PP-H	
ITEM	AV PP PIPES SDR11 PN10 15mm~200mm (d20~d225)			
DRAWN	E.Emmei	DATE	SCALE	
CHECKED	H.Kawano	FEB.27.2014	~	
APPROVED	K.Kamita	DRAWING No.		
SPECIAL ORDER No.	PK-60009DE		△	
ASAHI YUKIZAI CORPORATION				