



Note.

- Operating pressure 0.4-0.7MPa G
Air to open :Air-less shut
Air to shut :Air-less open
- The shape and appearance of assembly differ a little with nominal size compared to this drawing.

13	BOLT	4	SUS304(STAINLESS STEEL)	
12	ACTUATOR	1	PPG etc.	
11	STAND	1	PPG	
10	SCREW	4	SUS304(STAINLESS STEEL)	
9	STEM HOLDER	1	PP	
8	STEM	1	SUS403H(STAINLESS STEEL)	
7	O-RING	4	EPDM	
6	O-RING	1	EPDM	
5	SEAT	1	EPDM	
4	BUSH	1		
3	BUSH	1	BODY/DISC·BUSH □PVC/PP	
2	DISC	1	□PP/PP □PVDF/PVDF	
1	BODY	1		
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

DIMENSIONS TABLE

UNIT : mm

NOMINAL SIZE		d	DIN PN10			L	D	D1	D2	H	H1	A	A2	A3	A3'	P	ACTUATOR TYPE	
			C	n	h												AIR TO OPEN	AIR TO SHUT
40mm	1 1/2"	45	110	4	18	39	150	71	100	240	75	254	42.5	57	67	1/4	AR063NC17SN	AR063NO17SN
50	2	56	125	4	18	42	165	81	100	250	83	254	42.5	57	67	1/4	AR063NC17SN	AR063NO17SN
65	2 1/2	69	145	4	18	46	185	95	100	260	93	254	42.5	57	67	1/4	AR063NC17SN	AR063NO17SN
80	3	77	160	8	18	46	211	105	100	293	106	438	58.5	59	69	1/4	AR070NC17SN	AR070NO17SN
100	4	102	180	8	18	56	238	134	100	308	119	438	58.5	59	69	1/4	AR070NC17SN	AR070NO17SN
125	5	129	210	8	18	66	255	169	140	366	128	569	82.0	82	92	1/4	AR100NC22XN	AR100NO22XN
150	6	150	240	8	22	71	285	190	140	381	143	569	82.0	82	92	1/4	AR100NC22XN	AR100NO22XN
200	8	195	295	8	22	87	350	242	140	444	175	688	101.0	101	111	1/4	AR125NC22XN	AR125NO22XN

ITEM	BUTTERFLY VALVE TYPE 57 PNEUMATIC MODEL TYPE AR Ass'y		
	□AIR TO OPEN, □AIR TO SHUT		
	DIN PN10 40mm (1 1/2") ~ 200mm (8")		
	OPTION:		
DRAWN	N. Ito	DATE	SCALE
CHECKED	Y. Sato	Nov. 1, 2023	~
APPROVED	K. Koushou	DRAWING No. 57-AA106DE	
SPECIAL ORDER No.			
ASAHI YUKIZAI CORPORATION			