

**Safety Data Sheet**

Conforms to JIS Z 7253 : 2019

Preparation date: May 14, 2010

Revision date: Apr. 13, 2026

Page : 1/8

**1. Chemicals and Company Information**

<b>Product identifier</b>	AV CEMENT 52 (high-viscosity quick-drying up)
<b>SDS No.</b>	No.D-002
<b>Supplier name</b>	Asahi Yukizai Corporation
<b>Address</b>	2-5955, Nakanose-cho Nobeoka-city Miyazaki-pref. Japan 882-8688
<b>Phone number</b>	+81-982-35-9374 (EHS Management Department Valve & Piping Systems Division)
<b>Fax number</b>	+81-982-35-9357 (EHS Management Department Valve & Piping Systems Division)
<b>Emergency phone number</b>	+81-982-35-9374
<b>Manufacturer</b>	Konishi Co., Ltd.
<b>Recommended use and restrictions on use</b>	Adhesive for PVC pipes. Use only as specified.

**2. Hazards Identification****GHS classification**

Physical hazards	Flammable liquids	Category 2
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Skin sensitization	Category 1
	Germ cell mutagenicity	Category 2
	Carcinogenicity	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity (single exposure)	Category 1 (respiratory system)
	Specific target organ toxicity (single exposure)	Category 2 (central nervous system, kidneys)
	Specific target organ toxicity (single exposure)	Category 3 (Narcosis)
Specific target organ toxicity (single exposure)	Category 3 (Respiratory tract irritation)	
Specific target organ toxicity(repeated exposure)	Category 1 (respiratory system, central nervous system, digestive tract, bone, nervous system)	

The hazard class classified as "No classification" and "Classification not possible" has not been indicated.

Hazard pictograms(GHS JP)



GHS02



GHS07



GHS08

**Safety Data Sheet**

Conforms to JIS Z 7253 : 2019

Preparation date: May 14, 2010

Revision date: Apr. 13, 2026

Page : 2/8

<b>Signal word (GHS JP)</b>	Danger
<b>Hazard statement (GHS JP)</b>	Highly flammable liquid and vapour. (H225) Causes skin irritation. (H315) May cause an allergic skin reaction. (H317) Causes serious eye irritation. (H319) May cause respiratory irritation. (H335) May cause drowsiness or dizziness. (H336) Suspected of causing genetic defects. (H341) Suspected of causing cancer. (H351) Suspected of damaging fertility or the unborn child. (H361) Causes damage to organs (respiratory system, central nervous system).(H370) May cause damage to organs (kidneys). (H371) Causes damage to organs (bone, central nervous system, nervous system, liver, respiratory system) through prolonged or repeated exposure.(H372)
<b>Precautionary statements (GHS JP)</b>	
Prevention precautionary statements :	Obtain special instructions before use. (P201) Do not handle until all safety precautions have been read and understood.(P202) Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210) Keep container tightly closed. (P233) Ground and bond container and receiving equipment. (P240) Use explosion-proof electrical/ventilating/lighting equipment. (P241) Use only non-sparking tools. (P242) Take action to prevent static discharges. (P243) Do not breathe mist/vapours/spray. (P260) Avoid breathing mist/vapours/spray. (P261) Wash hands, forearms and face thoroughly after handling. (P264) Do not eat, drink or smoke when using this product. (P270) Use only outdoors or in a well-ventilated area. (P271) Contaminated work clothing should not be allowed out of the workplace.(P272) Wear protective gloves. (P280)
Response Precautionary Statements :	IF ON SKIN: Wash with plenty of water. (P302+P352) IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . (P303+P361+P353) IF INHALED: Remove person to fresh air and keep comfortable for breathing (P304+P340) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.(P305+P351+P338) IF exposed or concerned: Call a POISON CENTER or doctor.(P308+P311) IF exposed or concerned: Get medical advice/attention. (P308+P313) Call a POISON CENTER or doctor if you feel unwell. (P312) Get medical advice/attention if you feel unwell. (P314) Specific treatment (see supplemental first aid instruction on this label).(P321) If skin irritation occurs: Get medical advice/attention. (P332+P313) If skin irritation or rash occurs: Get medical advice/attention. (P333+P313) If eye irritation persists: Get medical advice/attention. (P337+P313) Take off contaminated clothing and wash it before reuse. (P362+P364) In case of fire : Use appropriate extinguishant for extinction.(P370+P378)

**Safety Data Sheet**

Preparation date: May 14, 2010

Revision date: Apr. 13, 2026

Conforms to JIS Z 7253 : 2019

Page : 3/8

Storage precautionary statements	Store in a well-ventilated place. Keep container tightly closed.(P403+P233) Store in a well-ventilated place. Keep cool. (P403+P235) Store locked up. (P405)
Disposal precautionary statements	Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. (P501)
Overview expected state of emergency	Organic solvent poisoning may be caused.

**3. Composition / Information on Ingredients**

Single or Mixture

Mixture

Generic name

Vinyl chloride resin adhesive

Component	Concentration(%)	Chemical formula	CAS-No.
Methyl ethyl ketone(MEK)	30-40%	C4H8O	78-93-3
Tetrahydrofuran	10-20%	C4H8O	109-99-9
Cyclohexanone	10-20%	C6H10O	108-94-1

**4. First-aid Measures**

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	Immediately call a POISON CENTER/doctor. Gently wash with plenty of soap and water. Take off immediately all contaminated clothing. Rinse skin with water/shower.
First-aid measures after eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
First-aid measures after ingestion	Rinse mouth. Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.
Protection of first-aiders	Do not attempt to take action without suitable protective equipment.

**5. Fire-fighting Measures**

Suitable extinguishing media	Dry chemical, CO2, or regular foam, Sand/earth
Unsuitable extinguishing media	Do not use a heavy water stream, Water
Fire hazard	Extremely flammable liquid and vapour.
Firefighting instructions	In case of fire: stop leak if safe to do so. Fight fire from safe distance and protected location
Personal protection (Emergency response)	Compressed air/oxygen apparatus, Fire-resistant protective clothing

**6. Accidental Release Measures****Personal Precautions, Protective Equipment and Emergency Procedures****For non-emergency personnel**

Protective equipment	Do not attempt to take action without suitable protective equipment.
Emergency procedures	Avoid contact with skin and eyes. Ventilate spillage area. Do not touch or walk on the spilled product. Prohibit unauthorized entry into the area.

**Safety Data Sheet****Environmental precautions**

Environmental precautions

Prevent entry to sewers and public waters.  
Do not allow to enter drains or water courses.  
Do not allow product to spread into the environment.

**Methods and Equipment for Containment and Cleaning up**

For containment

For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal.  
Stop leak without risks if possible.

Methods for cleaning up

Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.  
Absorb spilled material with sand or earth.  
Ground all equipment used to handle leakage.

**7. Handling and Storage****Handling**

Technical measures

Provide local ventilations and a full ventilation system as described in "Section 8".

Precautions for safe handling

Provide ventilation system and Use necessary personal protective equipment as described in "Section 8".  
Do not get in eyes, on skin, or on clothing.  
Do not breathe dust/fumes/gas/mist/vapours/spray.  
Ensure good ventilation of the work station.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
No open flame, No static electricity.  
Refer to "Section 10".

Hygiene measures

Always wash hands after handling the product.

**Storage precautionary statements**

Storage conditions

Store in a well-ventilated place. Keep container tightly closed.  
Protect from sunlight.

Storage temperature

2 – 40 °C

**8. Exposure controls / Protective measures**

<b>Methyl ethyl ketone(MEK)</b>	
Exposure limits (JSOH)	590 mg/m <sup>3</sup>
Exposure limits (JSOH)	200 ppm
MHLW Administration Level	200 ppm
<b>Tetrahydrofuran</b>	
Exposure limits (JSOH)	148 mg/m <sup>3</sup>
Exposure limits (JSOH)	50 ppm
MHLW Administration Level	50 ppm
<b>Cyclohexanone</b>	
Exposure limits (JSOH)	100 mg/m <sup>3</sup>
Exposure limits (JSOH)	25 ppm
MHLW Administration Level	20 ppm

Appropriate engineering controls

Ensure that there is a suitable ventilation system, Use local exhaust ventilation system.

Hand protection

Wear impermeable protective gloves. The following points should be considered in selecting protective gloves.  
Set the time of use that can be afforded for the work with reference to the impermeability class, etc. described in the instruction manual, and use

**Safety Data Sheet**

Preparation date: May 14, 2010

Revision date: Apr. 13, 2026

Conforms to JIS Z 7253 : 2019

Page : 5/8

Eye protection	protective gloves within the set time. Wear appropriate eye protection (glasses, glasses with side plates, goggles).
Skin and body protection	Wear long-sleeved work clothes and, if necessary, impermeable protective clothing and protective boots. The following points should be considered when selecting protective clothing and protective boots. Set the time of use that can be afforded for the work with reference to the impermeability class, etc. described in the instruction manual, and use protective gloves within the set time.
Respiratory protection	Wear appropriate respiratory protection for the situation. Consider wearing an air-supplied mask when handling high-concentration chemicals. Consider wearing respiratory protective equipment (gas mask, etc.) if workers are exposed to gas or vapor. The following points should be considered when selecting a gas mask. Do not use where oxygen concentration is less than 18%. When using a gas mask in an environment where workers are exposed to dust, use a gas mask with dust prevention function. Gas masks should have passed a type examination provided for registered agency for type examinations and structure suitable for work. At that time, refer to the data described in the instruction manual, etc.

**9. Physical and Chemical Properties**

Physical state	Liquid
Appearance	Liquid
Colour	Colorless translucent
Odour	Petroleum odor
pH	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	-14.5 °C closed-cup
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability	No data available
Explosive limits (Vol-%)	No data available
Vapour pressure	No data available
Relative vapour density at 20°C	≥ 1 (air = 1)
Relative density	No data available
Density	0.93 g/cm <sup>3</sup>
Relative gas density	No data available
Solubility	Insoluble in water. Soluble in organic solvents.
Partition coefficient octanol/ water (Log Pow)	No data available

# Safety Data Sheet

Conforms to JIS Z 7253 : 2019

Preparation date: May 14, 2010

Revision date: Apr. 13, 2026

Page : 6/8

Viscosity, dynamic	800 – 1500 mPa · s
Measured Temperature	20 °C
Viscosity, kinematic	No data available
Particle size	No data available
Particle size distribution	No data available
Particle shape	No data available
Particle aspect ratio	No data available
Particle specific surface area	No data available

## 10. Stability and Reactivity

Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Stable under normal conditions of use.
Conditions to avoid	Not specifically applicable.
Incompatible materials	Oxidizing agent.
Hazardous decomposition products	Carbon monoxide.

## 11. Toxicological Information

Acute toxicity (oral)	classification not possible
Acute toxicity (dermal)	classification not possible
Acute toxicity (inhalation)	classification not possible (gas)
	classification not possible (Vapour)
	classification not possible (dust, mist)

<b>Methyl ethyl ketone(MEK)</b>	
LD50 oral	2737 mg/kg
LD50 dermal	6480 mg/kg
LC50 Inhalation - Rat (Vapours)	34.5 mg/l/4h
<b>Tetrahydrofuran</b>	
LD50 oral	1650 mg/kg
LC50 Inhalation - Rat (Vapours)	53.6 mg/l/4h
<b>Cyclohexanone</b>	
LD50 oral	800 mg/kg
LD50 dermal	947 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	32.1 mg/l/4h
LC50 Inhalation - Rat (Vapours)	9.8 mg/l/4h

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory sensitization	classification not possible

**Safety Data Sheet**

Conforms to JIS Z 7253 : 2019

Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Suspected of causing genetic defects.
Carcinogenicity	Suspected of causing cancer.
Reproductive toxicity	Suspected of damaging fertility or the unborn child.
STOT-single exposure	Causes damage to organs (respiratory system, central nervous system). May cause damage to organs (kidneys). May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	Causes damage to organs (bone, central nervous system, nervous system, liver, respiratory system) through prolonged or repeated exposure.
Aspiration hazard	No classification

**AV CEMENT 52**

Viscosity, kinematic	860.215 – 1612.903 mm <sup>2</sup> /s
----------------------	---------------------------------------

**12. Ecological information**

Ecology - general	Dangerous for the environment if discharged into watercourses.
Hazardous to the aquatic environment, short-term (acute)	classification not possible
Hazardous to the aquatic environment, long-term (chronic)	classification not possible

**Methyl ethyl ketone(MEK)**

LC50 - Fish [1]	100 mg/l
EC50 - Crustacea [1]	1000 mg/l
ErC50 algae	1200 mg/l
NOEC chronic algae	93 mg/l

**Tetrahydrofuran**

LC50 - Fish [1]	2160 mg/l
EC50 - Crustacea [1]	5930 mg/l
NOEC chronic fish	216 mg/l

**Cyclohexanone**

LC50 - Fish [1]	527 mg/l
EC50 - Crustacea [1]	800 mg/l

**AV CEMENT 52**

Persistence and degradability	No data available
Bioaccumulative potential	No data available
Mobility in soil	No data available

**Hazardous to the ozone layer** classification not possible

**13. Disposal Considerations**

Residual Waste If you would like to dispose of this chemical, you should properly

**Safety Data Sheet**

Conforms to JIS Z 7253 : 2019

Preparation date: May 14, 2010




Revision date: Apr. 13, 2026

Page : 8/8

## Contaminated Container and Packaging

dispose of this by yourself or ask qualified specific agents dispose of this according to related legislations and local regulations. If you would like to ask the agents dispose of this chemical, you should provide sufficient information on dangerousness and hazard of this chemical. Container should be recycled after cleaning or if you would like to dispose of container of this chemical, you should properly dispose of this by yourself or ask qualified specific agents dispose of this according to related legislations and local regulations. If you would like to ask the agents dispose of this container, you should provide sufficient information on dangerousness and hazard of this chemical in this container and information on ingredient and notice of container.

**14. Transport Information****International regulations**

Road transport (UN RTDG)	Marine transport (IMDG)	Air transport (IATA)
<b>UN No.</b>		
1133	1133	1133
<b>UN official product name</b>		
Adhesives	ADHESIVES	Adhesives
<b>Classification of dangerous goods for transportation</b>		
3	3	3
		
<b>Packing group</b>		
II	II	II
<b>Environmental hazards</b>		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No

Marine pollutant

No

Special transport precautions

Please refer to "Section 7" in detail,

Under loading, containers must be carefully handled to prevent damage of containers and must be fixed them tightly to prevent falling of containers.

**15. Regulatory Information**

Regulatory information with regard to this substance in your country or region should be examined by your own responsibility.

**16. Other Information**

NOTICE : This SDS was made out as English translated version of the SDS based on the Japanese laws and regulations. Therefore, it was not applicable to the domestic distribution in the importing country.