

Safety Data Sheet

1. Products and Company Information

Product identifier	AV PIPE SU Type High Purity Type : Shavings
SDS No.	No.D-032
Supplier name	Asahi Yukizai Corporation
Address	2-5955, Nakanose-cho Nobeoka-city Miyazaki-pref. Japan 882-8688
Phone number	+81-982-35-9380 (CS & Quality Section EHS & CS/QA Department Valve & Piping Systems Division)
Fax number	+81-982-35-9358 (CS & Quality Section EHS & CS/QA Department Valve & Piping Systems Division)
Emergency phone number	+81-982-35-9380
Recommended use and restrictions on use	High purity PVC+FRP composite piping material Electrolysis (purified salt water), others, high-purity chemicals

2. Hazards Identification

GHS classification and label elements of the product

Physical hazards This product is a molded product and is not subject to classification.

Health hazards Skin corrosion / irritation : Category 2
Serious eye damage / eye irritation : Category 2B

Items for which the GHS classification result is "Not applicable to classification" or "Cannot classify" are not listed .

GHS label elements Symbol (GHS JP)

Signal word (GHS JP)

Hazard statement (GHS JP) H315 : Causes skin irritation
H320 : Causes eye irritation

Precautionary statement (GHS JP) (Shavings)

Safety measures P260 : Do not breathe dust.
P264 : Wash hands, forearms and face thoroughly after handling.
P270 : Do not eat, drink or smoke when using this product.
P273 : Avoid release to the environment.
P281 : Use personal protective equipment as required.

First-aid measures P304+P340 : If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P308+P313 : If there is exposure or concern of exposure, get medical advice/attention.

Storage P401 : Store not to leak of the Shavings.

Disposal P501 : Dispose of contents/container in accordance with local/national regulation.

Summary of significant signs and possible emergencies

3. Composition / Information on Ingredients

Single or Mixture	Solid mixture
Product name	AV PIPE SU Type : High Purity Type

Safety Data Sheet

Preparation date: Nov. 22, 2017

Conforms to JIS Z 7253 : 2019

Revision date: Mar. 08, 2022

Component	Concentration or concentration range	Chemical formula	Reference Number in Gazetted List in Japan		CAS No.
			CSCL (Chemical Substances Control Law)	Labor Safety and Health Act	
Polyvinyl chloride (PVC)	40 ~ 90%	(CH ₂ CHCl) _n	(6)-66	Che(6)-66	9002-86-2
Tin and its compounds	0.1-2%	-	Non-disclosure	Non-disclosure	Non-disclosure
Titanium(IV) oxide	< 1%	TiO ₂	(1)-558	Non-disclosure	13463-67-7
Carbon black	< 1%	-	(5)-5222	-	1333-86-4
Glass Fiber	3-30%	-	-	-	65997-17-3
Other organic/inorganic compounds	35%	-	Non-disclosure	Non-disclosure	Non-disclosure

Industrial Safety and Health Act

Hazardous and harmful materials requiring notification of name etc.
 (Article 57-2 of the Law, Enforcement Ordinance, Article 18-2, Schedule 9)
 Tin and its compounds (Legally specified number: 322) (0.1 and < 1%)
 Titanium oxide (IV) (Legally specified number: 191) (0.1 and < 1%)
 Carbon black (Legally specified number: 130) (0.1 and < 1%)

4. First-aid Measures**Description of first-aid measures****If inhaled (shavings)**

Move to a place of fresh air and get rest in an easily breathing posture.
 Call a doctor if you feel unwell.

If on skin (shavings)

Promptly remove the shavings.
 If you feel unusual, contact a doctor.

If in eyes (shavings)

Carefully wash with water for a few minutes.
 Remove contact lenses, if present and easy to do. Continue rinsing.
 If you feel unusual, contact a doctor.

If swallowed (shavings)

Rinse mouth.
 Contact a doctor immediately.
 Do not force him to vomit.
 If you feel unusual, contact a doctor.

Most Important Symptoms

Powder is irritating to the respiratory tract when inhaled in large quantities.
 May cause mild respiratory distress with prolonged or repeated exposure.

Protection of first responders

In case of powders, rescuers should wear protective equipment such as protective gloves and glasses.

Special precautions for physicians

None in particular

5. Fire-fighting Measures**Extinguishing media****Suitable extinguishing media**

Water, spray water, fire-extinguishing powder, general fire-extinguishing foam, carbon dioxide, sand.

Extinguishing media that should not be used

None in particular

Specific hazards in case of fire

It is self-extinguishing and disappears spontaneously when moved away from the flame. However, when it burns, it produces irritating gases.

(The main components of the gas are HCl, CO, and CO₂).

[Sourced from] Japan PVC Pipe and Fittings Association,
 Vinyl Environmental Council

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

Preparation date: Nov. 22, 2017

Revision date: Mar. 08, 2022

Specific fire extinguishing methods	Prohibit anyone other than related personnel from entering the area around the fire. If possible, move away from the source of the fire and extinguish it from upwind.
Protective equipment for fire-fighters	Wear appropriate protective clothing (heat-resistant) when extinguishing fires.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal precautions If dust is generated by pipe cutting, workers should wear appropriate protective equipment to avoid eye and skin contact and inhalation.

Environmental precautions

Environmental precautions Be careful not to discharge into rivers, etc., so as not to cause environmental impact.
It must not be discharged into the environment.

Containment and remediation methods and equipment

Containment methods If pipe cutting generates dust, it should be swept up and collected in an empty container for later disposal processing.
Remediation methods and Equipment Remove the dust by vacuuming or other methods that do not scatter the dust.

Prevention of secondary hazards

If dust is generated by pipe cutting, dispose of it frequently as it may cause slipping hazards if left on the floor.

7. Handling and Storage

Handling (Shavings)

Engineering measures Implement equipment measures as described in "**8. Exposure controls/Personal protection**" and wear protective equipment.

Implement local / general ventilation as described in "**8. Exposure controls/Personal protection.**"

Precautions for safe handling

Handle the product in such a way that no dust is generated.
Do not inhale dust. (Cutting dust).
Wash hands thoroughly after handling.
Use exhaust ventilation to keep airborne concentrations below exposure limits. (If dust is generated by pipe cutting)
Use outdoors or in a well-ventilated area.
Avoid release to the environment (when dust is generated by pipe cutting).

Contact avoidance

When dust is generated, take measures against static electricity for equipment and devices.
See "**10. Stability and Reactivity.**"

Storage (Shavings)

Engineering measures Store in a cool, dark, well-ventilated place away from direct sunlight and avoid fire.

Safe storage conditions

Paper bags, flexible containers, silos

8. Exposure controls/Personal protection

Control concentration, allowable concentration

Component	Control concentration	Allowable concentration (Japan Society for Occupational Health Version 2013)	Allowable concentration (ACGIH) (Version 2006)

Safety Data Sheet

Preparation date: Nov. 22, 2017

Conforms to JIS Z 7253 : 2019

Revision date: Mar. 08, 2022

Carbon black	2.9 mg/m ³	Inhalant dust 1mg/m ³ Total dust 4mg/m ³	3.5 mg/m ³
Titanium(IV) oxide	-	Inhalant dust : 1mg/m ³ Total dust : 4mg/m ³	10mg/m ³
Tin and its compounds	-	-	TWA 0.1 mg/m ³ STEL 0.2 mg/m ³ (As Tin)
Glass Fiber	3.0 mg/m ³	Inhalant dust : 2mg/m ³ Total dust : 8mg/m ³	-

Permissible concentration [Permissible concentration in case of powder, etc.]

Permissible concentration in case of powder, etc.	Japan Society for Occupational Health Version 2017	Ministry of Health, Labour and Welfare No. 1024-1 (2017.10.24)	ACGIH (Version 2017) : Polyvinyl chloride (Respirable Fraction)
Poly vinyl chloride (vinyl chloride resin)	Class 3 Dust Inhalable dust : 2mg/m ³ Total dust : 8mg/m ³	Organic and inorganic powdery substances General control guidelines Inhalable dust : 2mg/m ³	Inhalable dusts TWA : 1mg/m ³

[Working environment measurement]

Although these substances are not required by law to be measured in the working environment, efforts should be made to confirm and protect the working environment using working environment measurements and risk assessment tools.

Equipment measures

Install local exhaust ventilation in work areas where dust is generated. Install shower, hand washing, and eye washing facilities near the handling area. (If dust is generated by cutting)

Protective equipment**Respiratory protection**

Use personal respiratory protective equipment where necessary.

Hand protection

Use personal hand protective equipment where necessary.

Eye protection

Use personal eye protective equipment where necessary.

Skin and body protection

Use personal protective clothing and protective face mask as necessary.

Sanitary measures

Wash hands thoroughly after handling.

Special precautions

None in particular

9. Physical and Chemical Properties

Physical state**Appearance**

Solid (Pipe) (Cutting debris and dust are generated during cutting)

Color

Dark gray

Odor

Almost odorless

pH

No data available

Flash point

No data available

Specific gravity

1.6-1.7 (20 °C)

Combustion quality

Self-extinguishing

Solubility

No data available

Spontaneous ignition temperature

No data available

10. Stability and Reactivity

Reactivity

It is stable under normal handling.

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

Preparation date: Nov. 22, 2017

Revision date: Mar. 08, 2022

Chemical stability	It is stable under normal handling.
Possibility of hazardous reactions	When burned, it produces irritating gas (HCl).
Conditions to avoid	No information
Incompatible materials	Keep away from fire.
Hazardous decomposition products	When burned, it produces toxic gases (the main components of the gases are HCl, CO, and CO ₂).

11. Toxicological Information

Under a general environment it is a solid pipe showing no hazardous cases. However, the following items may apply to shavings and fragments that may occur during pipe installation.

Acute toxicity (oral)	Not classifiable due to the lack of data
Acute toxicity (dermal)	Not classifiable due to the lack of data
Acute toxicity (inhalation)	Not classifiable due to the lack of data
Skin corrosion / irritation	Class 2
Serious eye damage / eye irritation	Class 2B
Respiratory sensitization	Not classifiable due to the lack of data
Skin sensitization	Not classifiable due to the lack of data
Germ cell mutagenicity	Not classifiable due to the lack of data
Carcinogenicity	Not classifiable due to the lack of data
Reproductive toxicity	Not classifiable due to the lack of data
Toxicity of specific targets (single exposure)	Not classifiable due to the lack of data
Toxicity of specific targets (repeated exposure)	Not classifiable due to the lack of data
Aspiration hazard	If inhaled or aspirated in large quantities as a powder, the following hazards may occur depending on the particle size. Aspirable dusts (Dust collected by a sampler with a granulation characteristic of 50% cut of 100 μm) Dusts that settle in the airways and may cause airway irritation.

12. Environmental Information

Biotoxicity	No information
Residual and degradability	It does not readily decompose in the general environment.
Bioaccumulative	No information
Mobility in the soil	No information
Hazardous to the ozone layer	Not classifiable due to the lack of data
Other	When disposing of the product, follow the instructions in "13. Disposal Considerations".

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

Preparation date: Nov. 22, 2017

Revision date: Mar. 08, 2022

13. Disposal Considerations

Waste from residues

Follow the related laws and regulations as well as the local government's standards for disposal.

Entrust disposal to an industrial waste disposer licensed by the prefectural governor, or to a local public body, if such a body is in charge of disposal.

When consigning the disposal of waste to a contractor, the contractor should be fully informed of the hazards and harmfulness of the waste.

This product is classified as waste plastic (stable industrial waste).

Reference: Incinerate in an incineration facility with exhaust gas treatment equipment or landfill as non-hazardous waste. (Source: Japan Vinyl Chloride Industry and Environment Association, "Safety Information on Vinyl Chloride Resin")

Contaminated container and package (shavings) Not applicable

14. Transport Information

International regulations

Marine Pollutants No restrictions

Special transport precautions No restrictions

Domestic Regulations

Land Regulations Information No restrictions

Maritime Regulation Information No restrictions

Aviation Regulations Information No restrictions

Safety measures related to transportation or means of transportation

Follow "7. Handling and Storage "

15. Regulatory Information (in Japan) (Shavings)

Industrial Safety and Health Law Hazardous and Harmful Materials Requiring Notification (Article 57-2 of the Law; Enforcement Ordinance, Article 18-2, Schedule 9)

PRTR Law Not applied

Waste Management and Public Cleansing Act Industrial waste (classification for disposal as waste)

Poisonous and Deleterious Substances Control Act Not applied

Fire Service Act Not applicable or non-hazardous material

Foreign Exchange and Foreign Trade Act Not applied

Ship Safety Act Not applied

Civil Aeronautics Act Not applied

Act on Port Regulations Not applied

16. Other Information

Material Safety Data Sheets are provided to businesses that handle hazardous chemical products as reference information to ensure safe handling. Business operators who handle such products are requested to use this data sheet as a reference, with the understanding that it is necessary to take appropriate measures according to the actual conditions of individual handling, etc., on their own responsibility.

Therefore, this data sheet itself is not a guarantee of safety.

In addition, this information is subject to revision based on new findings.

Safety Data Sheet

Information on content, physical/chemical properties, etc. is not a guaranteed value.

The evaluation of hazards and harmfulness is based on materials and data currently available, but is not exhaustive.

If you have a Material Safety Data Sheet for this product that was previously provided to you, please destroy it.

SDSs may be revised due to legal revisions or product improvements. If the SDS was created or revised more than two years ago, please check that it is the latest version.

SDS transmission route : In principle, Safety Data Sheets (SDS) are transmitted to end users through the following route.

If you have not obtained the SDS yet, please contact us through the sales channel to request the SDS or to inquire about the latest version.

(Manufacturer agency handling business)

Disclaimer

The information contained in this sheet is based on reliable information, but no warranty, express or implied, is given as to the accuracy of the information. Because the conditions under which the product is handled, used, stored, or disposed of are beyond our control and may not be known to us, we assume no responsibility, direct or indirect, for any loss, damage, or expense resulting from the handling, use, storage, or disposal of the product. This sheet should be used only with this product. If this product is used as an ingredient in other products, the information contained in this sheet may not apply.