



DIMENSIONS TABLE

Unit: mm

Nominal Size		DIN PN10				L	D	D <sub>1</sub>	D <sub>2</sub>	H	H <sub>1</sub>	H <sub>2</sub>	I	Actuator Type	Motor Rating Output (Kw)
d	C	n	h												
300 <sup>mm</sup>	12"	303	400	12	22	129	488	360	235	387	244	301	671	LTRM-01/BRM-1 or LTRH-01/BRM-1 (AUTO-RECOVERY TYPE) (MANUAL RECOVERY TYPE)	0.2
350	14	351	460	16	22	129	539	393	235	414	270	328	698		

NOTE. The shape and appearance of assembly differ a little with nominal size compared to this drawing.

No.	DESCRIPTION	QTY.	MATERIAL	REMARKS
1a	RING	2	Steel 400 Unichrome Coated	Used for PP, PVDF Body.
204	GASKET (O)	1	EPDM	
39	BOLT (K)	4	STAINLESS STEEL (SUS304)	
36	STEM BUSH	1	CARBON STEEL (S45C)	
35	ACTUATOR	1	DUCTILE IRON (FCD450) etc.	Epoxy Coat.
7	STEM	1	□ STAINLESS STEEL (SUS403) □ STAINLESS STEEL (SUS316)	
185	O-RING (I)	4	□ EPDM □ FKM □ Others	
6	O-RING (C)	1	( )	
3	SEAT	1		
184	SEAT BUSH (B)	1	BODY / DISC SEAT BUSH	
183	SEAT BUSH (A)	1		
2	DISC	1	□ PVC / PP □ PP / PP □ PVDF / PVDF	
1	BODY	1		

ITEM	BUTTERFLY VALVE (TYPE57) ELECTRIC ACTUATED S TYPE ASS'Y □ AUTO-RECOVERY TYPE, □ MANUAL RECOVERY TYPE DIN PN10 300 <sup>mm</sup> (12") · 350 <sup>mm</sup> (14")		
DRAWN	M.Iwakiri	DATE	SCALE
CHECKED	H.Kawano	JUL.23.2018	~
APPROVED	K.Koushou	DRAWING No. 57-AE009DE	
SPECIAL ORDER No.	ASAHI YUKIZAI CORPORATION		