

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

1. Chemicals and Company Information

Product identifier	AV Adhesive 52 (high-viscosity quick-drying up)
SDS No.	No.D-002
Supplier name	Asahi Yukizai Corporation
Address	2-5955, Nakanose-cho Nobeoka-city Miyazaki-pref. Japan 882-8688
Phone number	+81-982-35-9380 (EHS Management Department Valve & Piping Systems Division)
Fax number	+81-982-35-9358 (EHS Management Department Valve & Piping Systems Division)
Emergency phone number	+81-982-35-9380
Manufacturer	Konishi Co., Ltd.
Recommended use and restrictions on use	Adhesive for PVC pipes. Use only as specified.

2. Hazards Identification

GHS classification and label elements of the product

Physical hazards	Flammable liquids	: Category 2
Health hazards	Skin corrosion/irritation	: Category 2
	Serious eye damage/eye irritation	: Category 2A
	Skin sensitization	: Category 1
	Germ cell mutagenicity	: Category 2
	Carcinogenic	: Category 2
	Reproductive toxicity	: Category 2
	Specific target organ toxicity (single exposure)	: Category 1 (respiratory system, central nervous system)
	Specific target organ toxicity (single exposure)	: Category 2 (kidney)
	Specific target organ toxicity (single exposure)	: Category 3 (Anesthetic effect)
	Specific target organ toxicity (single exposure)	: Category 3 (airway irritability)
	Specific target organ toxicity (repeated exposure)	: Category 1 (bone, central nervous system, nervous system, liver, respiratory system)

Items for which the GHS classification result is "Not applicable to classification" or "Cannot classify" are not listed.

GHS label elements Symbol (GHS JP)



GHS02



GHS07



GHS08

Signal word (GHS JP)

Danger

Hazard statement (GHS JP)

H225 : Highly flammable liquid and vapor

H315 : Causes skin irritation

H317 : May cause allergic skin reactions.

Safety Data Sheet

Preparation date: May 14, 2010

Revision date: June 16, 2023

Conforms to JIS Z 7253 : 2019

Page : 2/9

H319 : Causes serious eye irritation
 H335 : May cause respiratory irritation
 H336 : May cause drowsiness or dizziness.
 H341 : Suspected risk of hereditary disease
 H351 : Suspected of causing cancer
 H361 : Suspected of causing adverse effects on fertility or the unborn child.
 H370 : Organ damage (respiratory system, central nervous system)
 H371 : Risk of organ damage (kidney)
 H372 : Organ damage due to long-term or repeated exposure (bones, central nervous system, nervous system, liver, respiratory system)

Precautionary statement (GHS JP)**Safety measures**

P201 : Obtain the instruction manual before use.
 P202 : Do not handle until all safety precautions have been read and understood.
 P210 : Keep away from heat / sparks / open flames / hot surface.
 - No smoking.
 P233 : Keep container tightly closed.
 P240 : The container shall be grounded and earthed.
 P241 : Use explosion-proof electrical/ventilating/lighting equipment.
 P242 : Use tools that do not generate sparks.
 P243 : Take measures against electrostatic discharge.
 P260 : Do not inhale mists/vapors/sprays.
 P261 : Avoid inhalation of mist/vapor/spray.
 P264 : Wash hands, forearms and face thoroughly after handling.
 P270 : Do not eat, drink or smoke when using this product.
 P271 : Use only outdoors or in a well-ventilated area.
 P272 : Contaminated work clothing should not be removed from the workplace.
 P280 : Wear protective gloves.

First-aid measures

P302+P352 : If on skin , wash with plenty of soap and water.
 P303+P361+P353 : If on skin (or hair) , take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 : If inhaled, remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 : If in eyes, rinse cautiously with water for several minutes.
 Remove contact lenses, if present and easy to do.
 Continue rinsing.
 P308+P311 : If there is exposure or concern of exposure, contact a physician.
 P308+P313 : If there is exposure or concern of exposure, get medical advice/attention.
 P312 : Call a doctor if you feel unwell.
 P314 : Get medical advice/attention if you feel unwell.
 P321 : Specific treatment is required.
 P332+P313 : If skin irritation occurs, get medical advice/attention.
 P333+P313 : If skin irritation or rash occurs, get medical advice/attention.
 P337+P313 : If eye irritation persists, get medical advice/attention.
 P362+P364 : Take off contaminated clothing and wash it before reuse.
 P370+P378 : In case of fire, use appropriate media other than water for extinction.

Storage

P403+P233 : Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 : Store in a well-ventilated place. Keep cool.
 P405 : Store locked up.

Disposal

P501 : Dispose of contents/container in accordance with local/national regulation.

Summary of significant candidates and possible emergencies

The product may cause organic solvent poisoning.

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

3. Composition / Information on Ingredients

Single or Mixture

Mixture

Product name

Vinyl chloride resin adhesive

Component	Concentration or concentration range	Chemical formula	Reference Number in Gazetted List in Japan		CAS No.
			CSCL (Chemical Substances Control Law)	Labor Safety and Health Act	
Methyl ethyl ketone	30-40%	CH ₃ CH ₂ COCH ₃	(2)-542	-	78-93-3
Tetrahydrofuran	10-20%	C ₄ H ₈ O	(5)-53	-	109-99-9
Cyclohexanone	10-20%	C ₆ H ₁₀ O	(3)-2376	-	108-94-1

4. First-aid Measures

Description of first-aid measures

If inhaled

Remove person to fresh air and keep comfortable for breathing.
Get a doctor/physician if you feel unwell.

If on skin

Call a doctor immediately.
Wash gently with plenty of soap and water.
Remove all contaminated clothing immediately.
Wash skin with running water/shower.

If in eyes

Rinse cautious with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
Call a doctor immediately.

If swallowed

Rinse mouth.
Contact a physician immediately.
Do not induce vomiting.

Protection of first-aiders

Wear appropriate protective equipment.

5. Fire-fighting Measures

Extinguishing media

Suitable extinguishing media

Powdered chemical fire extinguisher, carbon dioxide or ordinary foam fire extinguisher, sand/soil.

Un suitable extinguishing media

Do not use direct water jet.

Fire Hazards

Extremely flammable liquid and vapor.

Extinguishing Measures

In the event of fire, stop the leak if it can be safely handled.
Conduct fire fighting from a safe distance and protected location.

Protective equipment for fire-fighters

Compressed air and oxygen breathing apparatus
Wear fire/flame resistant/retardant clothing.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Non-emergency responder

Protective equipment

Wear appropriate protective equipment when working.

First aid measures

Avoid contact with skin and eyes.

Ventilate spilled area.

Do not touch or walk on spilled product.

Prohibit entry of non-related personnel.

Environmental precautions

Safety Data Sheet

Preparation date: May 14, 2010

Revision date: June 16, 2023

Conforms to JIS Z 7253 : 2019

Page : 4/9

Environmental precautions

Prevent entry into sewers and public waterways.
Prevent entry into drains or waterways.
Do not release the product into the environment.

Containment and cleanup methods and equipment**Containment methods**

In the event of a large spill, contain the spill in a trench and block it with moist sand or earth for safe disposal afterwards.
Contain the leak without risk if possible.

Purification methods

If a small amount of liquid is spilled, absorb it with a nonflammable absorbent and place it in a container for disposal.
Absorb all diffused product with sand or soil.
Ground all equipment used when handling spills.

7. Precautions for Handling and Storage

Handling**Engineering measures**

Use local exhaust ventilation and general ventilation as described in "**8. Exposure controls / Protective measures**".
Take equipment measures as described in "**8. Exposure controls / Protective measures**" and wear protective equipment.

Precautions for safe handling

Do not get on eyes, skin, or clothing.
Do not inhale dust/smoke/gas/mist/vapor/spray.
Ensure adequate ventilation of work area.
Keep away from ignition sources such as heat/sparks/open flames/high temperature items.
—No smoking.
No fire and pay attention to static electricity.
Refer to "**10. Stability and Reactivity.**"

Sanitary measures

Always wash your hands after handling.

Storage**Safe storage conditions**

Store in a well-ventilated area.
Keep container tightly closed.
Keep out of sunlight.

Storage temperature

2-40 °C

8. Exposure controls / Protective measures

Methyl ethyl ketone (78-93-3)	
Control concentration (MHLW)	200ppm
Allowable concentration (Japan Society for Occupational Health)	200ppm (590mg/m ³)
ACGIH	TWA 200ppm, STEL 300ppm

Tetrahydrofuran (109-99-9)	
Control concentration (MHLW)	50ppm
Allowable concentration (Japan Society for Occupational Health)	50ppm (148mg/m ³)(skin)
ACGIH	TWA 50ppm, STEL 100ppm (Skin)

Safety Data Sheet

Cyclohexanone (108-94-1)	
Control concentration (MHLW)	20ppm
Allowable concentration (Japan Society for Occupational Health)	25ppm (100mg/m ³)
ACGIH	TWA 20ppm, STEL 50ppm (Skin)

Equipment measures

Provide adequate ventilation.
Install a local exhaust system.

Hand protection

Impervious protective gloves shall be worn. In selecting protective gloves, the following points should be considered
Set the time of use that is sufficient for the work with reference to the impermeability class, etc. listed in the instruction manual, and use the protective gloves within that time.

Eye protection

Wear appropriate eye protection (ordinary eyeglass type, ordinary eyeglass type with side plates, goggle type).

Protective equipment for skin and body

Wear long-sleeved work clothes, impervious protective clothing and protective boots if necessary.
The following points should be considered in selecting protective clothing and protective boots.
Set a use time that is sufficient for the work with reference to the impermeability class, etc. listed in the instruction manual, and use protective equipment within that time.

Respiratory protection

Wear appropriate respiratory protection for the situation. When handling highly concentrated chemical substances, consider wearing an air-supply respirator. If workers are exposed to gases or vapors, consider wearing respiratory protective equipment (e.g., gas masks). The following points should be considered when selecting a gas mask
Do not use in areas where the oxygen concentration is less than 18%. When using a gas mask in an environment where workers are exposed to dust, use an absorbent can with dustproof function.
Select a gas mask with performance and construction suitable for the work, conforming to the Japanese Industrial Standard (JIS T8152). In doing so, refer to the data described in the instruction manual, etc.

9. Physical and Chemical Properties

Physical state	Liquid
Appearance	Liquid
Color	Colorless and semitransparent
Odor	Petroleum odor

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

pH	No data
Melting point	No data
Freezing point	No data
Boiling point	No data
Flash point	-14°C (minimum ignition point used)
Spontaneous combustion point	No data
Decomposition temperature	No data
Flammability	No data
Explosion limits (vol%)	No data
Steam pressure	No data
Relative density	No data
Relative Vapor density (20°C)	1 or more (air =1)
Density	0.93g/cm ³
Relative gas density	No data
Solubility	Insoluble in water, soluble in organic solvent
n-octanol/water partition coefficient (LogPow)	No data
Kinematic viscosity	800 ~ 1500 mPa·s
Dynamic viscosity measurement temperature	20°C
Dynamic viscosity rate	No data
Particle size	No data
Particle diameter distribution	No data
Particle shape	No data
Particle aspect ratio	No data
Particle specific surface area	No data

10. Stability and Reactivity

Reactivity	Under normal conditions of use, storage and transportation, this product will not react.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Stable under normal conditions of use.
Conditions to avoid	Not applicable.
Incompatible materials	Avoid contact with oxidizer.
Hazardous decomposition products	Carbon monoxide (CO).

11. Toxicological Information

Acute toxicity (oral)	Cannot classify
Acute toxicity (dermal)	Cannot classify
Acute toxicity (inhalation)	Cannot classify (gas) Cannot classify (vapor)

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

Cannot classify (dust, mist)

Skin corrosion / irritation

Skin corrosion

Serious eye damage / eye irritation

Strong eye irritation

Respiratory sensitization

Cannot classify

Skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Suspected hereditary disease

Carcinogenicity

Suspected of causing cancer

Reproductive toxicity

Suspicion of adverse effects on reproductive functions or the fetus

Specific target organ toxicity (single exposure)

Organ damage (respiratory system, central nervous system)

Risk of organ damage (kidney)

May cause drowsiness or dizziness.

Risk of irritation to the respiratory tract

Specific target organ toxicity (repeated exposure) Organ damage due to long-term or repeated exposure (bones, central nervous system, nervous system, liver, respiratory system)**Aspiration hazard**

Not applicable to classification

12. Environmental Impact Information

Ecosystems - General

When leaking or disposing of the product, be careful not to handle it as it may affect the environment.

**Hazardous to the aquatic environment
Short-term hazard (Acute)**

Cannot classify

**Hazardous to the aquatic environment
Long-term hazard (Chronic)**

Cannot classify

AV Adhesive 52	
Residual and degradability	No data
Bioaccumulative	No data
Mobility in the soil	No data

Hazardous to the ozone layer

Cannot classify

13. Disposal Considerations

Contaminated container and package

Paper containers and packaging such as outer boxes and paper tubes:
Collected or disposed of as paper waste (If it is a single substance, it is treated as stable industrial waste. If there is an adhering component, it is also treated as controlled industrial waste too.)

When disposing of empty containers, remove the contents completely and dispose of them as industrial waste or send them for collection.

Metal can, metal drum, and metal tubes: Dispose of as scrap metal. (In the case of a single component, treat as stable industrial waste. If there are adhering components, follow the classification of stable/managed industrial wastes.)

Safety Data Sheet

Preparation date: May 14, 2010

Revision date: June 16, 2023

Conforms to JIS Z 7253 : 2019

Page : 8/9

Glass containers: Disposed of as glass waste. (In the case of a single component, treat as stable industrial waste. If there are adhering components, follow the classification of stable/managed industrial wastes.)

Plastic bottles, tubes, bags, etc.: Dispose as waste plastics. (In the case of a single component, treat as stable industrial waste. (If there are adhering components, follow the classification of stable/managed industrial wastes.)

Waste from residues




Dispose in accordance with applicable laws and regulations and municipal standards.

Entrust disposal to an industrial waste disposer licensed by the prefectural governor, or to a local public body, if such a body is in charge of disposal.

When disposing of waste, follow the Law Concerning Waste Disposal and Public Cleansing in particular.

When disposing of the product, confirm the reactivity of the hazardous information before processing.

14. Transport Information**International regulations**

Road transport (UN RTDG)	Marine transport (IMDG)	Air transport (IATA)
UN No.		
1133	1133	1133
UN official product name		
Adhesives	ADHESIVES	Adhesives
Classification of dangerous goods for transportation		
3	3	3
		
Packing group		
II	II	II
Environmental Hazardous		
Environmental Hazardous Not applicable	Environmental Hazardous Not applicable Marine Pollutants Not applicable	Environmental Hazardous Not applicable

Marine Pollutants

Not applicable

Special transport precautions

Follow the instructions in “7. Precautions for Handling and Storage”

Check that the containers are free from leakage and load them so as to prevent them from toppling over, falling, and suffering damage and ensure the prevention of cargo collapse.

Domestic Regulations**Land Regulations**

When the Fire Service Law, Industrial Safety and Health Law, or Poisonous and Deleterious Substances Control Law is applicable, the product shall be

Safety Data Sheet

Preparation date: May 14, 2010

Revision date: June 16, 2023

Conforms to JIS Z 7253 : 2019

Page : 9/9

transported in accordance with the applicable laws and regulations.

Maritime Regulation

Follow the provisions of the Ship Safety Law.

Aviation Regulations

Follow the provisions of the Civil Aeronautics Act.

Emergency Response Guideline Number

128

Other Information

No supplementary information

15. Regulatory Information (in Japan)**Industrial Safety and Health Law**

Second class organic solvent, etc. (Enforcement Ordinance, Schedule 6-2; Ordinance on the Prevention of Organic Solvent Poisoning, Article 1, Paragraph 1, Item 4)

Working Environment Assessment Standard
(Article 65-2, Paragraph 1 of the Law)

Hazardous and toxic substances whose names must be indicated
(Article 57-1 of the Law; Article 18 of the Enforcement Ordinance)

Hazardous / flammable material
(Enforcement Ordinance, Schedule 1, Item 4)

Hazardous and toxic substances whose names must be notified
(Article 57-2 of the Law; Enforcement Ordinance, Article 18-2, Schedule 9)

Cyclohexanone (Government Ordinance No.231) (20~30%)

Tetrahydrofuran (Government Ordinance No.367) (10~20%)

Methyl ethyl ketone (Government Ordinance No.570) (30~40%)

Poisonous and Deleterious Substances Control Law Not applicable

Fire Service Act

Category 4, Class 1 petroleum (water-insoluble) No fire Hazard class II

Foreign Exchange and Foreign Trade Act

Export Trade Control Order, Appended Table 1-16

Ship Safety Act

Flammable liquids (Regulations for the Carriage and Storage of Dangerous Goods in Ships, Articles 2 and 3; Hazardous Materials Notification, Schedule 1)

Civil Aeronautics Act

Flammable liquids (Civil Aeronautics Law Enforcement Regulations, Article 194; Hazardous Materials Notification - Schedule 1)

Act on Port Regulations

Other hazardous materials / flammable liquids (Article 21-2 of the Law; Article 12 of the Regulations; Notification specifying the types of dangerous goods, separate table)

Pollutant Release and Transfer Register

After revision April 1, 2023 and thereafter

Class 1 Designated Chemical Substances (Law Article 2, Paragraph 2, Enforcement Order Article 1, Appended Table 1)

Tetrahydrofuran (Control No. 674) (19%)

16. Other Information

The evaluation of hazards and hazardous properties is not always satisfactory, so please handle with care.

If you have a Safety Data Sheet for this product that was previously given to you, please destroy it.

The SDS is subject to revision due to changes in laws and regulations, product improvements, etc.

If the date of creation or revision is more than two years ago, please confirm that it is the latest version.

Safety Data Sheet

Conforms to JIS Z 7253 : 2019

Preparation date: May 14, 2010

Revision date: June 16, 2023

Page : 10/9

SDS transmission route : In principle, Safety Data Sheets (SDS) are transmitted to end users through the following route.

If you have not obtained the SDS yet, please contact us through the sales channel to request the SDS or to inquire about the latest version.

(Manufacturer → agency → handling business)

Disclaimer

The information contained in this sheet is based on reliable information, but no warranty, express or implied, is given as to the accuracy of the information. Because the conditions under which the product is handled, used, stored, or disposed of are beyond our control and may not be known to us, we assume no responsibility, direct or indirect, for any loss, damage, or expense resulting from the handling, use, storage, or disposal of the product. This sheet should be used only with this product. If this product is used as an ingredient in other products, the information contained in this sheet may not apply.