# Safety Data Sheet Conforms to JIS Z 7253 : 2019

No.D-017e-01 Page : 1/7 Preparation date: Nov. 22, 2017 Revision date: Mar. 08, 2022

#### **Products and Company Information** 1.

Product identifier	Chlorinated poly vinyl chioride pipes for hot and cold water supply : Shavings (JIS K 6776)		
SDS No.	No.D-017		
Supplier name	Asahi Yukizai Corporation		
Address	2-5955, Nakanose-cho Nobeoka-city Miyazaki-pref. Japan 882-8688		
Phone number	+81-982-35-9380 (CS & Quality Section		
	EHS & CS/QA Department Valve & Piping Systems Division)		
Fax number	+81-982-35-9358 (CS & Quality Section		
	EHS & CS/QA Department Valve & Piping Systems Division)		
Emergency phone number	+81-982-35-9380		
Recommended use and restrictions on use	Pipes for transfer of water at temperature not more than 90°C		

### 2. Hazards Identification

GHS classification and label elements of the p Physical hazards	roduct This product is a molded product and is not subject to classification.
Health hazards	Classification not possible
GHS label elements Symbol (GHS JP)	
Signal word (GHS JP)	
Hazard statement (GHS JP)	No information
Precautionary statement (GHS JP) (Shav	ings)
Safety measures	<ul> <li>P260 : Do not breathe dust.</li> <li>P264 : Wash hands, forearms and face thoroughly after handling.</li> <li>P270 : Do not eat, drink or smoke when using this product.</li> <li>P273 : Avoid release to the environment.</li> <li>P281 : Use personal protective equipment as required.</li> </ul>
First-aid measures	<ul><li>P304+P340 : If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing.</li><li>P308+P313 : If there is exposure or concern of exposure, get medical advice/attention.</li></ul>
Storage	P401 : Store not to leak of the Shavings.
Disposal	P501 : Dispose of contents/container in accordance with local/national regulation.
Summary of significant signs and possible emergencies	

## 3. Composition / Information on Ingredients

Single or Mixture	e Solid mixture				
Product name	Chlorinated poly vinyl chioride pipes for hot and cold water supply			supply	
Trade name	Super Pipe				
	Concentration or			ber in Gazetted Japan	
Component	concentration range	Chemical formula	CSCL (Chemical	Labor Safety and Health Act	CAS No.

Substances Control

# Safety Data Sheet Conforms to JIS Z 7253 : 2019

No.D-017e-01 Page : 2/7 Preparation date: Nov. 22, 2017 Revision date: Mar. 08, 2022

			Law)			
Heat-resistant vinyl chloride resin	85-90%	(CH2-CHCl)1-(CHCl-CHCl)m-(CH2-CCl2)n	(6)-75	Che(6)-75	68648-82-8	
Tin and its compounds	1-5%	Non-disclosure	Non-disclosure	Non-disclosure	Non-disclosure	
Other organic/inorganic compounds	1-10%	Non-disclosure	Non-disclosure	Non-disclosure	Non-disclosure	
Industrial Safety and Health Act		(Article 57-2 of the Law,	Hazardous and harmful materials requiring notification of name etc. (Article 57-2 of the Law, Enforcement Ordinance, Article 18-2, Schedule 9) Tin and its compounds (Legally specified number: 322) (1%)			
4. First-aid Meas Description of first-ai If inhaled (shaving	id measures	Move to a place of fresh a Call a doctor if you feel u		an easily breathin	g posture.	
If on skin (shavi	kin (shavings)Promptly remove the shavings.If you feel unusual, contact a doctor.					
If in eyes (shavings)Carefully wash with water for a few minutes.Remove contact lenses, if present and easy to do. Continue rinsiIf you feel unusual, contact a doctor.			insing.			
If swallowed (shavings)		Do not force him to vomi	Rinse mouth. Contact a doctor immediately. Do not force him to vomit. If you feel unusual, contact a doctor.			
			Powder is irritating to the respiratory tract when inhaled in large quantities. May cause mild respiratory distress with prolonged or repeated exposure.			
Protection of first responders In case of powders, rescuers should wear protective equipment			ipment such a			

protective gloves and glasses. Special precautions for physicians None in particular

### 5. Fire-fighting Measures

-		
Extin	guishing	g media

Suitable extinguishing media	Water, spray water, fire-extinguishing powder, general fire-extinguishing foam, carbon dioxide, sand.
Extinguishing media that should not be used	None in particular
Specific hazards in case of fire	It is self-extinguishing and disappears spontaneously when moved away from the flame. However, when it burns, it produces irritating gases. (The main components of the gas are HCl, CO, and CO <sub>2</sub> ). [Sourced from] Japan PVC Pipe and Fittings Association, Vinyl Environmental Council
Specific fire extinguishing methods	Prohibit anyone other than related personnel from entering the area around the fire. If possible, move away from the source of the fire and extinguish it from upwind.
Protective equipment for fire-fighters	Wear appropriate protective clothing (heat-resistant) when extinguishing fires.

# Safety Data Sheet Conforms to JIS Z 7253 : 2019

### No.D-017e-01 Page : 3/7 Preparation date: Nov. 22, 2017 Revision date: Mar. 08, 2022

### 6. Accidental Release Measures Personal precautions, protective equipment and emergency procedures

**Personal precautions** If dust is generated by pipe cutting, workers should wear appropriate protective equipment to avoid eye and skin contact and inhalation.

**Environmental precautions Environmental precautions** Be careful not to discharge into rivers, etc., so as not to cause environmental impact. It must not be discharged into the environment.

Containment and remediation methods and equipment			
Containment methods	If pipe cutting generates dust, it should be swept up and collected in an		
Remediation methods and Equipment	empty container for later disposal processing. Remove the dust by vacuuming or other methods that do not scatter the dust.		
Prevention of secondary hazards	If dust is generated by pipe cutting, dispose of it frequently as it may cause slipping hazards if left on the floor.		

#### Handling and Storage 7.

Handling (Shavings) Engineering measures	Implement equipment measures as described in "8. Exposure controls/Personal protection" and wear protective equipment.
	Implement local / general ventilation as described in "8. Exposure controls/Personal protection."
Precautions for safe handling	<ul> <li>Handle the product in such a way that no dust is generated.</li> <li>Do not inhale dust. (Cutting dust).</li> <li>Wash hands thoroughly after handling.</li> <li>Use exhaust ventilation to keep airborne concentrations below exposure limits. (If dust is generated by pipe cutting)</li> <li>Use outdoors or in a well-ventilated area.</li> <li>Avoid release to the environment (when dust is generated by pipe cutting).</li> </ul>
Contact avoidance	When dust is generated, take measures against static electricity for equipment and devices. See "10. Stability and Reactivity."
Storage (Shavings) Engineering measures	Store in a cool, dark, well-ventilated place away from direct sunlight and avoid fire.
Safe storage conditions	Paper bags, flexible containers, silos

## 8. Exposure controls/Personal protection

Control concentration, allowable concentration

Component	Control concentration	Allowable concentration (Japan Society for Occupational Health Version 2015)	Allowable concentration (ACGIH) (Version 2015)
Organic tin compound (As tin)	-	-	0.1 mg/m <sup>3</sup> (As tin)

### Permissible concentration [Permissible concentration in case of powder, etc.]

Permissible concentration in case of powder, etc.	Japan Society for Occupational Health Version 2017	Ministry of Health, Labour and Welfare No. 1024-1 (2017.10.24)	ACGIH (Version 2017) : Polyvinyl chloride (Respirable Fraction)
---	--	---	---

Chlorinated poly vinyl chioride pipes for hot and cold water supply : Shavings (JIS K 6776) ASAHI YUKIZAI CORPORATION

## Safety Data Sheet Conforms to JIS Z 7253 : 2019

No.D-017e-01 Page : 4/7 Preparation date: Nov. 22, 2017 Revision date: Mar. 08, 2022

	Poly vinyl chloride (vinyl chloride resin)	Class 3 Dust Inhalable dust : 2mg/ Total dust : 8mg/m <sup>3</sup>	n <sup>3</sup> Organic and inorganic powdery substances General control guidelines Inhalable dust : 2mg/m <sup>3</sup>	Inhalable dusts TWA :1mg/m <sup>3</sup>	
[Working environment measurement] Although these substances are not required by law to be measured working environment, efforts should be made to confirm and prote working environment using working environment measurements an assessment tools.			d be made to confirm and protect the		
Equi	Install sh		ocal exhaust ventilation in work areas where dust is generated. hower, hand washing, and eye washing facilities near the handling f dust is generated by cutting)		
Prot	ective equipment				
			Use personal respiratory protective equipment where necessary.		
Hand protection		Use pe	Use personal hand protective equipment where necessary.		
Eye protection		Use pe	Use personal eye protective equipment where necessary.		
Skin and body protection Use p		Use personal protective clothing and protective face mask as necessary.			
Sanitary measures W		Wash h	Wash hands thoroughly after handling.		
Special precautions None in p			particular		

### 9. Physical and Chemical Properties

Physical state	
Appearance	Solid (Pipe) (Cutting debris and dust are generated during cutting)
Color	Prown
Odor	Almost odorless
рН	No data available
Flash point	No data available
Specific gravity	Approx. 1.5 (20 °C)
Combustion quality	Self-extinguishing
(Combustible)	(It is a self-digestible resin with an oxygen index of about 45.)
Solubility	Insoluble in water. Insoluble in most organic solvents, but soluble in THF.
Spontaneous ignition temperature	Approx. 450°C

### 10. Stability and Reactivity

Reactivity	It is stable under normal handling.
Chemical stability	It is stable under normal handling.
Possibility of hazardous reactions	When burned, it produces irritating gas (HCl).
Conditions to avoid	No information
Incompatible materials	Keep away from fire.
Hazardous decomposition products	When burned, it produces toxic gases (the main components of the gases are $HCl$ , $CO$ , and $CO_2$ ).

#### **Toxicological Information** 11.

Under a general environment it is a solid pipe showing no hazardous cases. However, the following items may apply to shavings and fragments that may Chlorinated poly vinyl chioride pipes for hot and cold water supply : Shavings (JIS K 6776) ASAHI YUKIZAI CORPORATION

occur during pipe installation.

## **Safety Data Sheet**

Conforms to JIS Z 7253 : 2019

	011
Acute toxicity (oral)	Not classifiable du
Acute toxicity (dermal)	Not classifiable du
Acute toxicity (inhalation)	Not classifiable du
Skin corrosion / irritation	Not classifiable du
Serious eye damage / eye irritation	Not classifiable du
Respiratory sensitization	Not classifiable du
Skin sensitization	Not classifiable du
Germ cell mutagenicity	Not classifiable du
Carcinogenicity	Not classifiable du
Reproductive toxicity	Not classifiable du
Toxicity of specific targets (single exposure)	Not classifiable du
Toxicity of specific targets (repeated exposure)	Not classifiable du
Aspiration hazard	If inhaled or aspira may occur depend
	Aspirable dusts (D

Not classifiable due to the lack of data If inhaled or aspirated in large quantities as a powder, the following hazards may occur depending on the particle size.

Aspirable dusts (Dust collected by a sampler with a granulation characteristic of 50% cut of 100  $\mu$ m) Dusts that settle in the airways and may cause airway irritation.

### 12. Environmental Information

Biotoxicity	No information
Residual and degradability	It does not readily decompose in the general environment.
Bioaccumulative	No information
Mobility in the soil	No information
Hazardous to the ozone layer	Not classifiable due to the lack of data
Other	When disposing of the product, follow the instructions in "13. Disposal Considerations ".

### 13. Disposal Considerations

**Recyclable tubes** 

Waste from residues

In consideration of the environment, if it is possible to recycle, ask a recycling company to do so.

For pipes that cannot be recycled, comply with relevant laws and regulations and local government standards.

Entrust disposal to an industrial waste disposer licensed by the prefectural governor, or to a local public body, if such a body is in charge of disposal.

When consigning the disposal of waste to a contractor, the contractor should be fully informed of the hazards and harmfulness of the waste.

This product is classified as waste plastic (stable industrial waste).

Reference: Incinerate in an incineration facility with exhaust gas treatment

## Safety Data Sheet

Conforms to JIS Z 7253 : 2019

No.D-017e-01 Page : 6/7 Preparation date: Nov. 22, 2017 Revision date: Mar. 08, 2022

equipment or landfill as non-hazardous waste. (Source: Japan Vinyl Chloride Industry and Environment Association, "Safety Information on Vinyl Chloride Resin")

Contaminated container and package (shavings) Not applicable

### 14. Transport Information

International regulations	
Marine Pollutants	No restrictions
Special transport precautions	No restrictions
Domestic Regulations Land Regulations Information	No restrictions
Maritime Regulation Information	No restrictions
Aviation Regulations Information	No restrictions
Safety measures related to transportation or means of transportation	

Follow "7. Handling and Storage"

### 15. Regulatory Information (in Japan) (Shavings)

Industrial Safety and Health Low	Hazardous and Harmful Materials Requiring Notification (Article 57-2 of the Law; Enforcement Ordinance, Article 18-2, Schedule 9)
PRTR Law	Class 1 specified chemical substance (No. 305 Lead compounds)
Waste Management and Public Cleansing Act	Industrial waste (classification for disposal as waste)
Poisonous and Deleterious Substances Control Act	Not applied
Fire Service Act	Not applicable or non-hazardous material
Foreign Exchange and Foreign Trade Act	Not applied
Ship Safety Act	Not applied
Civil Aeronautics Act	Not applied
Act on Port Regulations	Not applied

### 16. Other Information

Material Safety Data Sheets are provided to businesses that handle hazardous chemical products as reference information to ensure safe handling. Business operators who handle such products are requested to use this data sheet as a reference, with the understanding that it is necessary to take appropriate measures according to the actual conditions of individual handling, etc., on their own responsibility.

Therefore, this data sheet itself is not a guarantee of safety.

In addition, this information is subject to revision based on new findings.

Information on content, physical/chemical properties, etc. is not a guaranteed value.

The evaluation of hazards and harmfulness is based on materials and data currently available, but is not exhaustive.

If you have a Material Safety Data Sheet for this product that was previously provided to you, please destroy it.

SDSs may be revised due to legal revisions or product improvements. If the SDS was created or revised more than two years ago, please check that it is the latest version.

SDS transmission route : In principle, Safety Data Sheets (SDS) are transmitted to end users through the following route.

If you have not obtained the SDS yet, please contact us through the sales channel to request the SDS or to inquire about the latest version.

(Manufacturer agency handling business)

## **Safety Data Sheet**

Conforms to JIS Z 7253 : 2019

No.D-017e-01 Page : 7/7 Preparation date: Nov. 22, 2017 Revision date: Mar. 08, 2022

Disclaimer

The information contained in this sheet is based on reliable information, but no warranty, express or implied, is given as to the accuracy of the information. Because the conditions under which the product is handled, used, stored, or disposed of are beyond our control and may not be known to us, we assume no responsibility, direct or indirect, for any loss, damage, or expense resulting from the handling, use, storage, or disposal of the product. This sheet should be used only with this product. If this product is used as an ingredient in other products, the information contained in this sheet may not apply.