



寸法表

単位: mm

呼び径	D (外径)			t (厚さ)		L (長さ)		1mあたりの重量 (参考) (kg/m)
	基準寸法	最大最小 外径許容差	平均外径 許容差	基準寸法	許容差	基準寸法	許容差	
13 ^{mm}	18.0	±0.2	±0.2	2.5	±0.2	4000	+30 -10	0.170
16	22.0	±0.2	±0.2	3.0	±0.3			0.251
20	26.0	±0.2	±0.2	3.0	±0.3			0.303
25	32.0	±0.2	±0.2	3.5	±0.3			0.439
30	38.0	±0.3	±0.2	3.5	±0.3			0.531
40	48.0	±0.3	±0.2	4.0	±0.3	4000 5000		0.774
50	60.0	±0.4	±0.2	4.5	±0.4			1.098
65	76.0	±0.5	±0.2	4.5	±0.4			1.415
75	89.0	±0.5	±0.2	5.9	±0.4			2.156
100	114.0	±0.6	±0.2	7.1	±0.5			3.338
125	140.0	±0.8	±0.3	7.5	±0.5	4.370		
150	165.0	±1.0	±0.3	9.6	±0.6	6.561		

JIS K 6742

		HI-PVC			
部番	名称	個数	材質	備考	
作図	岩切まゆみ	旭有機材株式会社			
検図	河野宏幸				
承認	甲正健二				
2021年3月10日		水道用耐衝撃性硬質塩化ビニル管 (HIVP) 13 ^{mm} ~ 150 ^{mm}			
尺度					
個別引合 No.					
納入先					
			図 番	PT-60022JJ	